

WETNESS INDICATOR FOR ALERTING A WEARER TO URINATIONBackground of the Invention

5 The present invention relates generally to absorbent articles, and more particularly to a wetness indicator for use in absorbent articles to alert a wearer to urination.

Disposable absorbent articles such as diapers, training pants, other child care products, other infant care products and adult care products are highly absorbent and efficiently pull moisture away from the wearer, reducing skin
10 irritation caused by prolonged wetness exposure. However, because these articles are so absorbent, wearers may not realize they have urinated, particularly if they are inexperienced toddlers who may not recognize the meaning of body sensations associated with urination. Thus, the wearer may not recognize their urination control failure or be aware the article should be changed. Many parents
15 believe that children must be given a signal such as feeling uncomfortable and wet to facilitate toilet training by making the child more aware that the act of urination has occurred. However, some parents worry about the possibility of skin irritations and rashes caused by prolonged wetness against the skin if the articles are less absorbent to allow the child to sense wetness.

20 Some prior absorbent articles intended for toilet training include means for alerting a child that urination has occurred without leaving a substantial amount of wetness against the skin. One such prior absorbent article includes a temperature changing element which allows the wearer to feel a change in temperature, alerting them after urination has occurred. Another example
25 includes an element which changes size after urination, expanding directly toward the wearer's crotch region. Still another example has high initial surface moisture immediately following urination but pulls moisture away from the wearer shortly thereafter.

Although there has been progress in articles for alerting a wearer to
30 urination, there continues to be a need for articles such as toilet training aids

which alert wearers to urination without allowing the skin to become wet.

Summary of the Invention

Generally, a wetness indicator of the present invention for alerting a
5 wearer to urination comprises a liquid permeable enclosure having a liquid
absorbent body therein. The absorbent body absorbs liquid in the presence
thereof and applies hydraulic pressure to the enclosure upon absorption of a
preselected amount of liquid. The enclosure limits expansion of the absorbent
body, stiffening the wetness indicator as liquid is absorbed. The wetness
10 indicator has a first stiffness when dry and a second stiffness greater than the first
stiffness upon absorption of the preselected amount of liquid.

The invention is further directed to a garment having an inner
surface facing a wearer when wearing the garment and a wetness indicator
generally as set forth above positioned relative to the inner surface for alerting the
15 wearer when the inner surface becomes wet with liquid.

Other features of the present invention will be in part apparent and
in part pointed out hereinafter.

Brief Description of the Drawings

20 Fig. 1 is a perspective of training pants having a wetness indicator of
the present invention therein;

Fig. 2 is a schematic top plan of unfolded training pants of a first
embodiment;

Fig. 3 is an enlarged schematic front elevation of a wetness
25 indicator of the present invention partially broken away to show interior details;

Fig. 4 is a schematic section of the wetness indicator taken in the
plane of line 4-4 of Fig. 3;

Fig. 5 is a schematic top plan of unfolded training pants of a second
embodiment;

Fig. 6 is a schematic top plan of unfolded training pants of a third embodiment;

Fig. 7 is a schematic top plan of unfolded training pants of a fourth embodiment; and

5 Fig. 8 is an enlarged schematic section of the training pants of the fourth embodiment taken in the plane of line 8-8 of Fig. 7.

Corresponding reference characters indicate corresponding parts throughout the several views of the drawings.

10 Definitions

Within the context of this specification, each term or phrase below includes the following meaning or meanings:

“Attached to” refers to the joining, adhering, connecting, bonding, or the like, of two elements. Two elements will be considered to be attached to one
15 another when they are attached directly to one another or indirectly to one another, such as when each is directly attached to intermediate elements.

“Bonded” refers to the joining, adhering, connecting, attaching, or the like, of two elements. Two elements will be considered to be bonded together when they are bonded directly to one another or indirectly to one another, such as
20 when each is directly bonded to intermediate elements.

“Layer” when used in the singular can have the dual meaning of a single element or more than one element.

“Superabsorbent” refers to a water-swellaable, water-insoluble organic or inorganic material capable, under the most favorable conditions, of
25 absorbing at least about fifteen times its weight and, more desirably, at least about thirty times its weight in an aqueous solution containing 0.9 weight percent sodium chloride. The superabsorbent materials can be natural, synthetic and modified natural polymers and materials, or a combination of such materials. In addition, the superabsorbent materials can be inorganic materials, such as silica
30 gels, or organic compounds such as cross-linked polymers.

Detailed Description of the Preferred Embodiments

Referring now to the drawings and more particularly to Fig. 1, a pair of toilet training pants, or more generally an absorbent article, is designated in its entirety by the reference numeral 21. The pants have a waist opening 25 and two leg openings 27. Where the pants 21 are worn, a crotch region, generally designated 31 and located generally between the leg openings 27, is generally positioned between the legs of the wearer. A front 33 of the training pants 21 extends generally upward from the crotch region 31, partially covering a lower abdomen of the wearer. A back 35 of the training pants 21 opposite the front 33 extends generally upward from the crotch region 31 to cover a buttocks of the wearer. The training pants 21 include an inner surface 36 facing the wearer and an outer surface 37 facing away from the wearer.

Various materials and methods for constructing training pants are disclosed in PCT Publication No. WO 00/37009 by Fletcher et al. published June 29, 2000; U.S. Patent No. 4,940,464 issued July 10, 1990, to Van Gompel et al.; and U.S. Patent No. 5,766,389 issued June 16, 1998, to Brandon et al.; all of which are hereby incorporated by reference. An example of such training pants is marketed under the mark PULL-UPS® training pants by Kimberly-Clark Corporation of Neenah, Wisconsin.

A wetness indicator for alerting a wearer to urination, generally designated by 39, is positioned generally between the leg openings 27 of the training pants 21. It should be understood that the wetness indicator 39 may be positioned elsewhere than in the crotch region 31 without departing from the scope of the present invention. It is envisioned that the position of wetness indicator 39 within the crotch region 31 may be different depending on whether the article is intended to be worn by girls or boys. As will be discussed in greater detail below, the wetness indicator 39 is configured to absorb liquid, such as urine. Therefore, placement in a more forward position of the crotch region 31 may be appropriate for boys, and placement in a more central position between the legs may be appropriate for girls. Before absorption of such liquid, the

wetness indicator 39 is pliable and virtually imperceptible to the wearer, as will be discussed in greater detail below.

Although the wetness indicator 39 of the present invention is illustrated in Fig. 1 as being used in toilet training pants 21, the wetness indicator
5 may also be used in conjunction with other garments and/or absorbent articles, such as underwear, diapers, and washable or reusable absorbent articles such as woven training pants, absorbent swim pants, plastic training pants, and the like. Further, although discussed primarily in the context of toilet training for children, it should be understood that the present invention is applicable to adult personal
10 care products such as absorbent incontinence undergarments and the like. The wetness indicator 39 may either be built directly into the article during manufacture or may be formed independently and attached to any of the aforementioned articles by the consumer. If the wetness indicator 39 is built directly into the article during manufacture, the wetness indicator may be
15 optionally releasably attached so the consumer can remove the wetness indicator if desired.

As illustrated in Fig. 2, a first embodiment of the wetness indicator 39 of the present invention is sized and shaped for positioning between the leg openings 27 of the pants 21. The training pants in Fig. 2 are depicted partially
20 disassembled and unfolded to a flat position. The lateral edges 45 of the pants 21 are disconnected, exposing the flattened inner surface 36 of the pants, or the portion of the pants facing the wearer when the garment is worn. The wetness indicator 39 is positioned relative the inner surface 36 for alerting the wearer when the pants become sufficiently wet with liquid. Typically, the wetness
25 indicator 39 is placed between the inner surface 36 and outer surface 37 (Fig. 1) to be hidden within the pants 21, such that the pliable wetness indicator is substantially imperceptible to the wearer before urination. However, those skilled in the art will appreciate the wetness indicator 39 may be positioned anywhere in the article where it is likely to become wet and be perceived by a wearer.

In one embodiment, the wetness indicator 39 is generally elongate, and remains elongate upon absorption of a preselected amount of liquid, as will be discussed in greater detail below. Although other orientations are contemplated as being within the scope of the invention, the wetness indicator 39 of one embodiment is oriented generally laterally within the garment, such that the longest dimension of the wetness indicator lies substantially parallel to a lateral axis A of the garment which extends between the leg openings 27. The periphery of the wetness indicator 39 of this embodiment is also generally rectangular in cross-section before absorption of the preselected amount of liquid, and after absorption, the wetness indicator becomes generally rounded. It is also contemplated that the wetness indicator 39 of the present invention may be formed in a shape other than a rectangle, without departing from the scope of the present invention.

Turning to the specific features of the wetness indicator 39, Figs. 3 and 4 illustrate one embodiment. The wetness indicator 39 comprises a liquid permeable enclosure 51 having a liquid absorbent body 55 therein. Generally, such a body 55 comprises a thin sheet material laid over itself at least once to form at least two folds. In one embodiment, the absorbent body 55 is formed from thin sheet material fan folded longitudinally multiple times (e.g., two times) along multiple longitudinal fold lines 59 (Fig. 4) to form a multifold structure. Such a fan folded structure enhances the strength of the absorbent body 55 because each fold of material will act to support adjacent folds, further magnifying the expansive pressure within the enclosure 51. As such, the overall strength and stiffness of the absorbent body 55 increases in the direction of the fold line. The absorbent body 55 may have at least one longitudinal fold line, thereby forming at least two folds of absorbent sheet material. By varying the number of fold lines and the width of the folds, differently sized and shaped absorbent bodies 55 are possible. In one embodiment, the outer cross-section of the wetness indicator is generally rectangular when dry, expanding to a roughly oval shape after absorption, and having a width W less than four times its height H upon

absorption of the preselected amount of liquid. For example, a square portion of material 6.4 centimeters (cm) per side and 0.065 cm thick is folded approximately in thirds to provide an absorbent body 55 having a width W of about 2.1 cm, a height H of about 0.195 cm and a length L of about 6.4 cm. The body 55 may be otherwise formed to facilitate expansion upon absorption of a preselected amount of liquid such as by being for placement within the enclosure 51. Other materials requiring no folds are also contemplated as within the scope of the present invention.

It is desirable that the absorbent body 55 be formed from a high absorbency under load (AUL) material. Although the absorbent body 55 may be made from other materials without departing from the scope of the present invention, in one embodiment the body is an Ultra Thin Absorbent (UTA) material comprising about fifty percent superabsorbent material and about fifty percent wood pulp and having a weight of about 225 grams per square meter (gsm) at a thickness of about 0.65 millimeter. One such UTA material can be produced using an online process such as described in U.S. Application number 09/939,061, entitled "Thin, High Capacity Absorbent Structure and Method for Producing Same," filed August 24, 2001, by Sawyer, et al., which claims priority from U.S. Provisional Application number 60/256,016, filed December 20, 2000, both of which are hereby incorporated by reference. In addition, U.S. Patent Nos. 5,147,343 (Kellenberger) and 5,601,542 (Melius et al.) describe other processes for producing UTA material. An alternate material is available from EAM Corporation of Jessup, Georgia, under the trademark NovaThin® material. Although other materials may be used to form the enclosure 51 without departing from the scope of the present invention, in one embodiment the liquid permeable enclosure is formed from 20 gsm spunbond nonwoven available from Kimberly-Clark Corporation, Neenah, Wisconsin. Such material may also be surface treated with about 0.45 weight percent of a surfactant mixture, such as AHCOVEL® N-62 chemical, available from Uniqema Inc., a division of ICI of New Castle, Delaware, or such as a surface treatment with an active ratio of about 3:1

of GLUCOPON® 220UP chemical, available from Cognis Corp. of Ambler, Pennsylvania. The surfactant may be applied to the entire surface of the spunbond nonwoven material, or it may be selectively applied to particular surface portions, such as to a surface portion facing the body. It is contemplated
5 that the enclosure 51 could also include liquid impermeable portions, such as those portions positioned away from the wearer without departing from the scope of the present invention.

When liquid flows through the liquid permeable enclosure 51 of the wetness indicator 39 and contacts the absorbent body 55, the liquid is absorbed
10 by the body. Capillary, osmotic and absorptive forces draw the liquid into the wetness indicator 39. This absorption process helps draw liquid away from the skin of the wearer. As the wetness indicator 39 absorbs the liquid, the absorbent body 55 within the enclosure 51 begins swelling. When dry, the wetness indicator 39 is generally soft, pliable and cloth-like with a first stiffness similar to the other
15 portions of the pants 21, making the presence of the wetness indicator 39 generally imperceptible to the wearer. The pliable wetness indicator 39 allows the thighs to move freely and easily compress the wetness indicator 39.

Once liquid is present in the pants 21 and the absorbent body 55 begins absorbing liquid, the absorbent body swells within the enclosure 51. Upon
20 absorption of a preselected amount of liquid, the absorbent body 55 applies hydraulic pressure against the interior of the enclosure 51. Because the unrestrained saturated volume of the absorbent body 55 is greater than the volume of the enclosure 57, the liquid permeable enclosure limits expansion of the absorbent body, thereby stiffening the wetness indicator 39. As more liquid is
25 absorbed by the body 55, the wetness indicator 39 becomes stiffer. Once the wetness indicator 39 absorbs the preselected amount of liquid, the wetness indicator reaches a second stiffness greater than the first stiffness. Such a stiffness provides a resistance to bending that may be readily perceived by the wearer.

Although the wetness indicator 39 may have other stiffnesses without departing from the scope of the present invention, in one configuration, tested previously and described below, the wetness indicator has a second stiffness about eleven times greater, on average, than its first stiffness. In
5 another configuration, tested previously and described below, the second stiffness is about fourteen times greater, on average, than its first stiffness. The method for obtaining these stiffness measurements is described in the experiments detailed below. An effective wetness indicator 39 should have a second stiffness at least about five times greater than its first stiffness.

10 For example, a wetness indicator 39 with an average dry length of about 11.5 cm, an average dry width of about 2.0 cm and an average dry thickness of about 0.5 cm and composed of the materials described herein was used. Although the second stiffness may be measured upon absorption of a different amount of liquid without departing from the scope of the present
15 invention, in one embodiment the second stiffness is measured upon absorption of about 33 grams of urine. However, those skilled in the art will appreciate that the amount of urine absorbed by the body 55 in actual use varies depending upon the size of the wetness indicator 39 and the materials used. In other words, the stiffness may be different in actual use.

20 The enclosure 51 of Figs. 3 and 4 limits expansion of the absorbent body 55 in order for the enclosure to reach the second stiffness. If the liquid permeable enclosure 51 were too expandable, absorption of the preselected amount of liquid would simply expand the wetness indicator 39 without causing it to lose some of its pliability. In use, the pants 21 can be designed with the
25 wetness indicator 39 positioned for resisting movement against the inner thighs of the wearer. Such resistive force exerted by the wetness indicator 39 upon the inner thighs is not large, but rather gently resists leg movement on the inside of the legs of the wearer such that the wearer perceives a resistive pressure, which he may learn to associate with urination. To further enhance the signaling
30 properties of the wetness indicator 39, the liquid permeable enclosure 51 can be

5 tightly wrapped about the liquid absorbent body 55. Wrapping the enclosure 51 tightly about the absorbent body 55, lowers the expandability of the absorbent body and decreases the amount of liquid required for the wetness indicator 39 to reach its second stiffness. The absorbent body 55 must not be wrapped too tightly, however, or the first stiffness of the wetness indicator 39 before absorbing liquid will be too great.

10 Furthermore, it is important that the preselected amount of liquid remain within the enclosure 51 even under outside pressure, such as applied by the leg of the wearer. If wearer movement forces liquid from the absorbent body 55 and out of the enclosure 51, the ability of the wearer to perceive a stiffened wetness indicator 39 decreases. Because the wearer may be active at the time of urination, the ability of the wetness indicator 39 to resist outside forces is key. If the amount of liquid in the enclosure 51 remains above the preselected amount, the hydraulic pressure within the enclosure, and therefore the stiffness of the wetness indicator 39, may be maintained continually for a sustained and perceptible indication that urination has occurred. Forming the absorbent body from an AUL material that resists releasing liquid, even under pressure.

20 Fig. 5 depicts a second embodiment of the training pants 21 of the present invention in which two elongate wetness indicators 39 extend parallel to one another within the training pants 21. Although one wetness indicator 39 may sufficiently signal the wearer when urination has occurred, it is envisioned additional wetness indicators may further enhance the signal to the wearer. These wetness indicators 39 may be necessary for larger or older children with larger legs, who may find the resistive force provided by a single wetness indicator provides insufficient resistive force for perception. Further, the presence of two wetness indicators 39 permits one wetness indicator to be positioned where it is more likely to become wet upon urination by boys and one wetness indicator to be positioned where it is more likely to become wet upon urination by girls, thereby compensating for differences between the wetting patterns of boys and girls.

25

30

Fig. 6 illustrates a third embodiment of the present invention. The third embodiment of the training pants 21 includes a wetness indicator 39 having a large width W compared to its length L. For instance, the wetness indicator 39 in one embodiment has a width W between about one-fourth its length L and about three-fourths its length upon absorption of the preselected amount of liquid. Because the wetness indicator 39 has a large width W, it may be capable of absorbing more liquid than the wetness indicators of the first and second embodiments described above. Thus, it is envisioned that the wetness indicator 39 may be the only absorbent wetness indicator used in the training pants 21 of the third embodiment. Because such a wetness indicator 39 is capable of absorbing more liquid, it may provide a larger resistive pressure to the wearer due to its size.

Figs. 7 and 8 depict a fourth embodiment of the present invention. Here, the training pants 21 include a liquid permeable enclosure 51 that has at least two chambers 65. Each chamber 65 contains a separate absorbent body 55 for absorbing liquid. In addition, each of the chambers 65 acts independently from the other chambers. In one embodiment, the chambers 65 are similarly sized and shaped, although differently sized and shaped chambers are also contemplated as being within the scope of the present invention. For instance, in the preferred embodiment, the chambers 65 are generally elongate and are oriented substantially parallel to each other. Such parallel chambers 65 act in concert by resisting flexure together against the legs of the wearer.

The chambers 65 are formed within the training pants 21 in a novel way. The enclosure 51 comprises a liquid permeable lining 69, which forms the inner surface 36 of the pants 21, and a base layer 73 bonded to one another along a series of parallel, spaced-apart seams 77, forming the chambers 65. These seams 77 may be formed by sonic bonding, with an adhesive or using any other conventional sealing process capable of forming seams between the lining 69 and the base layer 73. End portions 83 of the chambers 65 are also sealed (Fig. 7). Wetness indicators 39 having fewer or more chambers 65 are

contemplated as being within the scope of the present invention, and the number and orientation of the chambers shown in Figs. 7 and 8 are exemplary only.

As will be appreciated by those skilled in the art, the enclosure 51 described above may be an osmotic membrane and the absorbent body 55 may be a solution, a mixture, or a gel without departing from the scope of the present invention.

Experiment 1

An experiment was conducted to determine the change in stiffness of the wetness indicator from its first stiffness when dry to its second stiffness upon absorption of the preselected amount of liquid. The experiment entailed the use of ten sample wetness indicators having an average dry length of about 11.5 cm, an average dry width of about 2.0 cm and an average dry thickness of about 0.5 cm (not including the sonic seal about the edge as described below). The samples exhibited an average dry weight of about 2.6 grams. The samples were each formed as a liquid permeable enclosure having a liquid absorbent body therein. The liquid permeable enclosure comprised 20 gsm spunbond polyethylene available from Kimberly-Clark Corporation of Neenah, Wisconsin. The spunbond polyethylene was surface treated with about a 0.45 weight percent surfactant mixture containing AHCOVEL® N-62 chemical and about a 3:1 active ratio of GLUCOPON® 220UP chemical. The liquid absorbent body comprised about ten percent Kraton® G2740X polymer, available from Kraton Polymers U.S. LLC of Houston, Texas, sixty percent Favor® SXM 880 Super Absorbent Material from Stockhausen, Inc. of Greensboro, North Carolina, and thirty percent Sulfatate-HJ-FA Kraft, Southern Hardwood Pulp from Rayonier, Inc. of Jacksonville, Florida. The liquid absorbent body was generally formed as a sheet-like material 5 cm wide and 11 cm long, fan folded lengthwise into thirds and placed inside the liquid permeable enclosure. To help the absorbent body hold its shape, an adhesive transfer tape (Model No. 922XL, 1.3 cm wide, 0.05 millimeter thick adhesive transfer tape from 3M, Inc. of St. Paul, Minnesota) was

placed between the outermost layer of the absorbent body and the remainder of the absorbent body, to retain the body in its folded configuration. In addition, the material of the liquid permeable enclosure was sonically bonded to itself for about 0.1 seconds at a pressure of 150 kiloPascals on a Branson 920 Sonic Bonder, available from Branson Ultrasonics, Inc. of Danbury, Connecticut, forming an enclosure for the absorbent body.

For each of the ten samples tested, the sample was placed across a pair of upright supports spaced 5 cm apart with about 4 cm of each end of the wetness indicator extending over each support. The supports were placed upon a tared scale so that additional vertical loads could be recorded. A testing probe having a width greater than the width of the wetness indicator and a thickness of 0.2 cm was then pressed downward upon the wetness indicator midway between the supports, thereby bending the wetness indicator and deflecting the center of the wetness indicator downward. The probe deflected the wetness indicator about 1.2 cm down from the initial horizontal position and a reading was recorded from the scale. An increase in such a reading beyond the weight of the supports and the wetness indicator indicated the force required to bend the wetness indicator, or the relative stiffness of the wetness indicator.

Once the ten samples were deflected in their dry condition, the samples were each tested again after soaking for five minutes in a 0.9% by volume Aqueous Solution Isotonic Saline (i.e., Sodium Chloride) available from Ricca Chemical Company of Arlington, Texas. The saline solution served as an approximation of urine. The five minute soak time ensured adequate saturation of the sample. After absorption, each sample was drained for one minute on a paper towel. In the saturated condition, the length and width dimensions of the wetness indicator remained unchanged, about 11.5 cm by about 2.9 cm, respectively, while the thickness of the wetness indicator increased to about 2.0 cm. In addition, the cross-sectional shape of the wetness indicator changed from a flattened rectangle to a generally rounded shape. The sample was then placed

upon the supports for the same 1.2 cm deflection noted above, again recording the load on the scale during the deflection.

On average, the load recorded for the ten dry samples during deflection was 36 grams. Subtracting the average weight of the wetness indicators themselves, 2.6 grams, this portion of the experiment indicated that a load of about 33 grams was required to deflect the wetness indicator about 1.2 cm downward from the initial horizontal position. In contrast, the load recorded for the same ten samples after absorption indicated an average load during deflection of 405 grams. Subtracting the average weight of the wetness indicators after absorption, 25 grams, the deflection load for the wetness indicator was 380 grams, on average. Thus, after absorption of liquid, the wetness indicator described above is over eleven times stiffer in bending than in its dry condition ($380/33 = 11.5$). As used herein, "stiffness" means the force exerted upon the wetness indicator divided by the deflection. Here, where the deflection of each test was identical, the definition of stiffness is directly related to the recorded force. This experiment validated the assertion that the stiffness of the wetness indicator increased after absorption of liquid.

Experiment 2

An experiment was conducted to determine the change in stiffness of another wetness indicator from its first stiffness when dry to its second stiffness upon absorption of the preselected amount of liquid. The deflection experiment was essentially the same as noted above, except that the wetness indicator itself was formed differently. Here, the liquid absorbent body was formed from a sheet-like material 3.8 cm wide and 11 cm long, folded lengthwise into half and positioned inside the liquid permeable enclosure. The overall size of the wetness indicator was 11.5 cm long, 2.0 cm wide and 0.3 cm thick (not including the sonic seal around the edge). In the saturated condition, the length dimension of the wetness indicator remained unchanged, about 11.5 cm, while the thickness of the wetness indicator increased to about 1.5 cm and the width decreases to about 1.5

cm. In addition, the cross-sectional shape of the wetness indicator changed from a flattened rectangle to a more rounded shape, as with the wetness indicator of the first experiment.

On average, the load recorded for the ten dry samples during the
5 1.2 cm downward deflection from the initial horizontal position was 16 grams. Subtracting the average weight of the wetness indicators themselves, 2.2 grams, this experiment indicated a load of about 14 grams was required to deflect the wetness indicator in a dry condition about 1.2 cm. In contrast, the load recorded for the same ten samples after absorption indicated an average load during
10 deflection of 223 grams. Subtracting the average weight of the wetness indicators after absorption, 22 grams, the deflection load for the wetness indicator was 201 grams, on average. Thus, after absorption of liquid, the wetness indicator described above was over fourteen times stiffer in bending than in its dry condition ($201/14 = 14.4$). Therefore, a wetness indicator should provide a
15 second stiffness that is at least about five times greater than its first stiffness. More particularly, the second stiffness is between about five and about twenty-five times greater than the first stiffness. Preferably the second stiffness is between about ten and about fifteen times greater than the first stiffness.

Comparing the results of experiments 1 and 2, one skilled in the art
20 would readily understand how to create a wetness indicator of varying stiffness by altering the size, materials and shape of the experimental wetness indicators. The wetness indicators disclosed in experiments 1 and 2 are included for demonstrative purposes only and should not be construed to limit the scope of the present invention. For example, wetness indicators could easily be made longer,
25 shorter, thicker, thinner, wider, narrower or in a different configuration altogether without departing from the scope of the present invention.

When introducing elements of the present invention or the preferred embodiment(s) thereof, the articles "a", "an", "the", and "said" are intended to mean that there are one or more of the elements. The terms "comprising,"

“including”, and “having” are intended to be inclusive and mean that there may be additional elements other than the listed elements.

As various changes could be made in the above constructions without departing from the scope of the invention, it is intended that all matter
5 contained in the above description or shown in the accompanying drawings shall be interpreted as illustrative and not in a limiting sense.

10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
22